




Comparación de Dispositivos

		 X-Station	 Xpass	 Xpass S2	
main	Biometric	-	-	-	
	IP Rating	-	IP65	IP65	
	RF Option	125KHz EM 13.56MHz Mifare/DESFire	125KHz EM 125KHz HID Prox 13.56MHz Mifare/DESFire	13.56MHz Mifare/DESFire/Felica	
	Multi-Controller ¹	-	Y(RF Only)	Y ¹	
Capacity	Max. User (1:1)	200,000	40,000	50,000	
	Max. User (1:N)	200,000	40,000	50,000	
	Max. Template (1:1)	-	-	-	
	Max. Template (1:N)	-	-	-	
	Max. Text Log	1,000,000	50,000	100,000	
	Max. Image Log	5,000	-	-	
Interface	WiFi	-	-	-	
	TCP/IP	Yes	Yes	Yes	
	RS-485	1ch Host and Slave	1ch	1ch Host or Slave (Selectable)	
	RS-232	Yes ²	-	-	
	Wiegand	1ch In or Out (Selectable)	1ch In or Out (Selectable)	1ch In or Out (Selectable)	
	Input	2 Inputs	2 Inputs	2 Inputs	
	Relay	1 Relay	1 Relay	1 Relay	
	USB	-	-	-	
	SD Card Slot	-	-	-	
Hardware	CPU	667MHz RISC	533MHz DSP	533MHz DSP	
	Memory	128MB RAM + 1GB Flash	16MB RAM + 8MB Flash	16MB RAM + 16MB Flash	
	LCD	3.5" Touch	-	-	
	LED Indicator	-	Multi-Color	Multi-Color	
	Sound	16-bit Hi-Fi	Multi-tone Buzzer	Multi-tone Buzzer	
	Operating Temp	-20° to 50°C	-20° to 50°C	-35° to 65°C	
	Tamper	Yes	Yes	Yes	
	Power	12VDC	12VDC	12VDC	
	PoE	-	Optional	-	
	"Dimensions (W x H x D mm)"	79 x 135 x 21	45 x 130 x 27	80 x 120 x 11.4	
	Certificates	CE, FCC, MSIP(KCC), RoHS	CE, FCC, MSIP(KCC), RoHS	CE, FCC, MSIP(KCC), RoHS, REACH	
Compatibility ³	BioStar 1.x	Yes	Yes	Yes	
	BioStar 2	-	Yes	Yes	

¹ Max Capacity Varies with # of Fingerprint Templates Registered

² No Flow Control

³ Requires F/W Update